

Snap-Lock 1" is a low-profile concealed fastener panel with a clean, modern line. Panels snap together by hand and fasten through a hidden nail flange - no clips - so it goes on fast. A good fit for residential and light commercial roofs.



1"

SEAM HEIGHT

12" / 16" / 18"

COVERAGE

3 : 12

MIN. SLOPE

24 / 26


GAUGES

PANEL PROFILE MEASUREMENTS

Model	A Coverage	B Seam Height	C Actual Width
12" Panel	12"	1"	13 3/8"
16" Panel	16"	1"	17 3/8"
18" Panel	18"	1"	19 3/8"




PANEL INTERLOCKING



Snap-Lock Seam

Snaps closed by hand



Nail Flange

No clips - fastened through the flange

PANEL PROFILE OPTIONS



Flat

Can show oil-canning on long runs



Minor Striations



Major Striations

*Recommended

PANEL DATA

Min. Panel Length	36"
Max. Panel Length	50' / Custom
Min. Required Slope	3 : 12
Fastening	Nail flange - no clips
Standard Surface	Smooth

Gauge Options	24 / 26
Tapered Panels	Yes [optional]
Radiused Panels	No
Stiffening Ribs	Yes [optional]
Profile Options	Flat / Minor / Major Striations

PANEL GAUGE / COLOR / WARRANTY OPTIONS

Material	Gauge	Colors	Included Warranties	Optional Warranties
Galvalume® Steel	26	SMP Colors - Premium Textured, Premium Smooth, Architectural Expressions	40-Yr Limited Lifetime Finish + *10-Yr Weather Tight	*15-Yr Weather Tight
Galvalume® Steel	24	PVDF Colors - chart PENDING	40-Yr Limited Lifetime Finish + *10-Yr Weather Tight	*15-Yr Weather Tight

*Weather Tight Warranties must be registered within 30 days of roof completion. Optional terms: 15-Yr \$0.15 / sq ft, 20-Yr \$0.25 / sq ft. See the Michigan Metal Roofing Limited Lifetime and Weather Tight Warranty documents for full terms.

WEATHER TIGHT WARRANTY OPTIONS

INCLUDED

10 Year

No cost. Available on every Michigan Metal Roofing system.

OPTIONAL

15 Year

\$0.15 / sq ft. Snap-Lock and Mechanical Seam systems.

OPTIONAL

20 Year

\$0.25 / sq ft. Mechanical Seam only.

METAL SPECIFICATIONS & PAINT FINISHES

PENDING

Coil specifications (substrate, thickness per gauge, steel grade, coating weight and paint system) are coming from our coil supplier and will be added here.

STORAGE & HANDLING

Store panels in a dry, well-ventilated place. Moisture trapped between stacked panels - rain, snow or condensation - causes water staining and white rust, which shortens the life of the panel and ruins its appearance.

If panels have to be stored outside, cover them with a breathable tarp or waterproof paper, never plastic. Keep them off the ground on wood, tilted slightly so water drains. Protective film breaks down in direct sun - remove it promptly.

GENERAL USE & PRECAUTIONS

- Install in a sequential pattern.
- An approved underlayment is recommended over a solid deck.
- Install per industry-recognized sheet metal practice.
- Cut, form and fasten with conventional hand or power tools. Keep cutting edges sharp and aligned.
- Do not cut with power saws or abrasive blades.
- Panels are pre-finished - handle with care and never drag panels across each other.
- Remove protective film from concealed or joined areas before assembly.
- Not for areas of high abrasion or mechanical damage.

This sheet highlights Michigan Metal Roofing products and specifications and is subject to change without notice. Michigan Metal Roofing is responsible for providing quality materials that meet its published product specifications. Neither Michigan Metal Roofing nor its representatives practice architecture or engineering, and Michigan Metal Roofing offers no opinion on and disclaims any responsibility for the soundness of any structure. Consult a qualified structural engineer before installation if the structure's ability to support the planned installation is in question. No Michigan Metal Roofing representative is authorized to vary this disclaimer.